50

8MT30V-50

Fax: +370-5-2651483

Phone: +370-5-2651474

Narrow Motorized Translation Stage

with Vacuum compatible stepper motor

vitir vacaam companiste stepper motor

SPECIFICATIONS

Travel range 50 mm Lead screw pitch 0.25 mm Resolution in full step* $1.25 \mu m$ Max. speed* 2.5 mm/s Load capacity Horizontal 3 kg Vertical 1 kg Fluoroplastic cable integrated, 2 m length Motor connector HDB15(M) VSS42 Vacuum compatible stepper motor


Weight **Assemblies:**

X-Y 2CP173V-50-20 Z 2AB173V-20-50

Many applications require vacuum compatible stages. 8MT30V-50 stage is equipped with 10⁻⁶ Torr vacuum compatible stepper motor, all mechanical parts are lubricated with High vacuum compatible grease. Aluminum parts are not anodized. Stages are

cleaned in vacuum chamber and packed before dispatch, so that it can be immediately placed in vacuum chamber after purchase without spoiling the vacuum. Cleaning and packing not included in price.

Recommended Controllers



12,5

for Stepper Motor Stepper Motor

Stepper Motor Controller with USB Interface

8SMC1-USBhF

with DC motor

0.55 kg

Brushed DC Servo Motor Controller with USB Interface 8DCMC1-USB

M4 hole

for fixing screw

2 clearance holes

for M4 screw

cable with connector HDB15(M)/

11,5


Narrow Motorized Translation Stage

8MT30-50DCE

DC motor

90,5

DC motor



DC motor provides **smoother motion** and **closed loop operation**. High number of motor reduction gear provides high resolution, but low speed in turn. Ideal for applications demanding high accuracy but not sensitive to speed limitations.

5

41,1